

**TranzX**  
inspiring your ride

**TranzX**  
inspiring your ride

[www.tranzx.com](http://www.tranzx.com)

80, NAN DEE LANE,  
SHAN HSI VILLAGE, SHOU SHUI HSIANG,  
504 CHANG HUA HSIEN, TAIWAN R.O.C.

T : +886-4-7681756

F : +886-4-7680575

**2025**

[www.tranzx.com](http://www.tranzx.com)





# CONTENTS

ELECTRONIC	02
TRAVEL ADJUST	03
LIGHT WEIGHT	07
VALUE	08
PINOCCHIO	09
PERFORMANCE	10
SUSPENSION	13
EXTERNAL	16
LEVER	18



## JD-EDP01

ISO MTB / Pat.

Electronic Dropper Post with bluetooth connection, zero hassle of cable routing. Experience new tech within your reach.

Material	Alloy #7075-T651
Offset	0 mm.
Dia.	30.9 / 31.6 / 34.9
Length	395 mm. / Travel 125mm. 445 mm. / Travel 150mm. 485 mm. / Travel 170mm. 545 mm. / Travel 200mm.
Weight	730 g / 30.9 * 545 mm. 748 g / 31.6 * 545 mm. 684 g / 30.9 * 485 mm. 702 g / 31.6 * 485 mm. 654 g / 30.9 * 445 mm. 672 g / 31.6 * 445 mm. 616 g / 30.9 * 395 mm. 634 g / 31.6 * 395 mm. 66.5 g / Remote Lever 37.5 g / Battery Charger 19 g / Lithium Ion Battery
Finish	Sandblasted Black
Shaft finish	Hard Anodized Black




Up to 200 mm Travel



Electronic



Alloy 7075



Pressure Adjustable



Bluetooth



Remote Lever



Battery Charger



Li-ion Battery



Battery Cover



## JD-YSI35

ISO MTB

**NEW**

Premium dropper post features patented convex post head for shorter overall length and stack height, centered bottom actuator for better clearance, +RAD travel adjust bushing system

Material	Alloy #7075-T651
Offset	0 mm.
Dia.	30.9 / 31.6 / 34.9 mm.
Travel Adjust	25 mm. (5 mm. / step)
Length	30.9 / 31.6 348 mm. / Travel 110mm. 34.9 411 mm. / Travel 140mm. 451mm. / Travel 160 mm. 451 mm. / Travel 160mm. 491mm. / Travel 180 mm. 491 mm. / Travel 180mm. 551mm. / Travel 210 mm. 551 mm. / Travel 210mm.
Weight	652 g / 34.9 * 551 mm. 586 g / 30.9 * 551 mm. 597 g / 31.6 * 551 mm. (excluding cable set 90 g)
Finish	Sandblasted Black
Shaft finish	Hard Anodized Black



Internal Routing




Up to 210 mm Travel

+RAD Travel Adjust



Alloy 7075



Pressure Adjustable



**JD-YSI08**

ISO MTB

Premium dropper post with shorter overall length and stack height, featuring air valve to adjust rebound speed and +RAD for travel adjust fitment

Material	Alloy #7075-T651
Offset	0 mm.
Travel Adjust	25 mm. (5 mm. / step)
Dia.	30.9 / 31.6 / 34.9 mm.
Length	387 mm. / Travel 125 mm. 442 mm. / Travel 150 mm. 482 mm. / Travel 170 mm. 542 mm. / Travel 200 mm. 612 mm. / Travel 230 mm.
Weight	570 g / 30.9 * 542 mm. 500 g / 30.9 * 442 mm. 645 g / 34.9 * 542 mm. (excluding cable set 90 g)
Finish	Polished Black
Shaft finish	Hard Anodized Back

**JD-YSI20**

ISO MTB

Long travel 27.2 dropper post with travel adjust feature

Material	Alloy #7075-T651
Offset	0 mm.
Dia.	27.2 mm.
Travel Adjust	25 mm. (5 mm. / step)
Length	400 mm. / Travel 100 mm. 450 mm. / Travel 125 mm.
Weight	440 g / 27.2 * 450 mm. 410 g / 27.2 * 400 mm. (excluding cable set 90 g)
Finish	Polished Black
Shaft finish	Hard Anodized Black

**JD-YSI05J**

ISO MTB / Pat.

Adjustable Travel Dropper Post with patented bushing, allowing adjustment for better fitment to different rider's height

Material	Alloy #7075-T651
Travel Adjust	30 mm. (5 mm / step)
Offset	0 mm.
Dia.	30.9 / 31.6 / 34.9 mm.
Length	409 mm. / Travel 125 mm. to 95 mm. 459 mm. / Travel 150 mm. to 120 mm. 499 mm. / Travel 170 mm. to 140 mm. 559 mm. / Travel 200 mm. to 170 mm.
Weight	575 g / 30.9 * 459 mm. 595 g / 31.6 * 459 mm. (excluding cable set 90 g)
Finish	Sandblasted Black
Shaft finish	Hard Anodized Black



**+RAD**  
TRAVEL ADJUST



**JD-YSI15**

ISO MTB

Award winning integrated seat clamp dropper post without the need for custom frame, and infinite travel adjust for wide range of rider's fitment

<b>Material</b>	Alloy #7075-T651
<b>Offset</b>	0 mm.
<b>Dia.</b>	30.9 / Seat Clamp Dia. 34.9 mm. 31.6 / Seat Clamp Dia. 34.9 mm. 34.9 / Seat Clamp Dia. 38.6 or 38.9 mm.
<b>Length</b>	660 mm. / Travel 225 mm. 602 mm. / Travel 200 mm. 547 mm. / Travel 175 mm. 492 mm. / Travel 150 mm. 432 mm. / Travel 125 mm.
<b>Weight</b>	808 g / 31.6 * 660 mm. / Travel 225 mm. 785 g / 30.9 * 660 mm. / Travel 225 mm. 745 g / 31.6 * 602 mm. / Travel 200 mm. 726 g / 30.9 * 602 mm. / Travel 200 mm. 702 g / 31.6 * 547 mm. / Travel 175 mm. 682 g / 30.9 * 547 mm. / Travel 175 mm. 890 g / 34.9 * 660 mm. / Travel 225 mm. 826 g / 34.9 * 602 mm. / Travel 200 mm. 773 g / 31.6 * 547 mm. / Travel 175 mm.
<b>Finish</b>	Polished Black
<b>Shaft finish</b>	Hard Anodized Black

**JD-YSI16**

ISO MTB

Light weight dropper post suitable for XC, gravel, all road application


<b>Material</b>	Alloy #7075-T651 (27.2) Alloy #6066-T6 (30.9&31.6)
<b>Offset</b>	0 mm
<b>Dia.</b>	27.2 / 30.9 / 31.6
<b>Length</b>	27.2 340 mm. / Travel 70 mm. 390 mm. / Travel 70 mm. 390 mm. / Travel 100 mm. 30.9 / 31.6 350 mm. / Travel 70 mm. 350 mm. / Travel 100 mm. 400 mm. / Travel 70 mm. 400 mm. / Travel 100 mm.
<b>Weight</b>	27.2 382 g * 340 mm. / Travel 70 mm. 412 g * 390 mm. / Travel 70 mm. 412 g * 390 mm. / Travel 100 mm. 31.6 439 g * 350 mm. / Travel 70 mm. 430 g * 350 mm. / Travel 100 mm. 465 g * 400 mm. / Travel 70 mm. 473 g * 400 mm. / Travel 100 mm. (excluding cable set 90 g)
<b>Finish</b>	Polished Black / Sandblasted Black (27.2 mm.)
<b>Shaft finish</b>	Hard Anodized Black

**JD-YSI36**

ISO MTB

Ultra light weight dropper post suitable for XC, gravel, all road application

<b>Material</b>	Alloy #6066-T6 (Travel 100 & 120 mm.) Alloy #7075-T615 (Travel 150, 170, 200 mm.)
<b>Offset</b>	0 mm.
<b>Dia.</b>	30.9 / 31.6
<b>Length</b>	328 mm. / Travel 100 mm. 390 mm. / Travel 100 mm. 373 mm. / Travel 120 mm. 436 mm. / Travel 150 mm. 479 mm. / Travel 170 mm. 545 mm. / Travel 200 mm.
<b>Weight</b>	376 g / 31.6 * 328 mm. / Travel 100 mm. 411 g / 31.6 * 373 mm. / Travel 120 mm. 412 g / 31.6 * 390 mm. / Travel 100 mm. 469 g / 31.6 * 436 mm. / Travel 150 mm. 498 g / 31.6 * 479 mm. / Travel 170 mm. 556 g / 31.6 * 545 mm. / Travel 200 mm. (excluding cable set 90 g)
<b>Finish</b>	Polished Black
<b>Shaft finish</b>	Hard Anodized Black



**JD-YSP18P**

ISO MTB ★ / Pat.

Entry level internal routing post with competitive cost and high quality balance.

Material	Alloy #6061-T6
Offset	0 mm.
Dia.	30.9 / 31.6 mm.
Length	318 mm. / Travel 80 mm. 361 mm. / Travel 100 mm. 403 mm. / Travel 120 mm. 425 mm. / Travel 130 mm. 470 mm. / Travel 150 mm. 515 mm. / Travel 170 mm.
Weight	560 g / 30.9 * 403 mm. 580 g / 31.6 * 403 mm. (excluding cable set 90 g)
Finish	Polished Black
Shaft finish	Hard Anodized Black

★ stage 2 standard according to suspension system

**JD-YSI34**

ISO MTB

Exceptional value and quality dropper post in 34.9 optimised size

Material	Alloy #6061
Offset	0 mm.
Dia.	34.9 mm.
Length	349 mm. / Travel 100 mm. 399 mm. / Travel 125 mm. 456 mm. / Travel 150 mm. 496 mm. / Travel 170 mm. 556 mm. / Travel 200 mm.
Weight	493 g / 349 mm. 524 g / 399 mm. 599 g / 456 mm. 633 g / 496 mm. 685 g / 556 mm. (excluding cable set 90 g)
Finish	Polished Black
Shaft finish	Hard Anodized Black

**JD-YSP01V**

ISO MTB ★

AM bike adjustable seat post - Freely, fit the terrain you meet! The Pinocchio tool less height MICRO adjustable post offers a quick and easy lowering task.

- \* Reliable and solid technology - Virtually No Play!
- \* Exquisite elegant and easy assembling w/low profile head design

Material	Alloy #7075-T651 & SAE4130 (27.2 mm.) Alloy #6061-T6 (30.9 / 31.6 mm.)
Offset	15 mm.
Dia.	27.2 / 30.9 / 31.6 mm.
Length	340 mm. / Travel 80 mm. (27.2 mm.) 390 mm. / Travel 100 mm. (27.2 mm.) 318 mm. / Travel 80 mm. (30.9 / 31.6 mm.) 361 mm. / Travel 100 mm. (30.9 / 31.6 mm.) 402 mm. / Travel 120 mm. (30.9 / 31.6 mm.)
Weight	615 g / 30.9 * 400 mm. 623 g / 27.2 * 390 mm.
Finish	Polished Black Sandblasted Black (27.2 mm.)
Shaft finish	Hard Anodized Black (30.9 / 31.6 mm.) QPQ (27.2 mm.)

★ stage 2 standard according to suspension system

**JD-YSP50**

ISO MTB

Entry level dropper post suitable for city, trekking, or cargo bikes; offering the ease to adjust saddle height and safer with feet on the ground while bike stop.

Material	Alloy #6061-T6
Offset	12 mm.
Dia.	27.2 / 30.9 / 31.6 mm.
Length	400 mm. / Travel 50 mm. (27.2 mm.) 357 mm. / Travel 100 mm. (30.9 / 31.6 mm.) 403 mm. / Travel 120 mm. (30.9 / 31.6 mm.) 472 mm. / Travel 150 mm. (30.9 / 31.6 mm.) 518 mm. / Travel 170 mm. (30.9 / 31.6 mm.)
Weight	589 g / 27.2 * 400 mm. 795 g / 31.6 * 518 mm.
Finish	Polished Black Sandblasted Black
Shaft finish	Hard Anodized Black



**JD-YSP32J**

ISO MTB / Pat.

Premium level dropper post with lighter weight and rebound speed adjustable feature.

Material	Alloy #7075-T651
Offset	0 mm.
Dia.	30.9 / 31.6 mm.
Length	350 mm. / Travel 100 mm. 400 mm. / Travel 125 mm. 458 mm. / Travel 150 mm. 498 mm. / Travel 170 mm. 558 mm. / Travel 200 mm.
Weight	535 g / 30.9 * 458 mm. 555 g / 31.6 * 458 mm. (excluding cable set 90 g)
Finish	Polished Black
Shaft finish	Hard Anodized Black

**JD-YSP23J**

ISO MTB / Pat.

Performance level dropper post for riders that don't compromise on the functionality with excellent price point.

Material	Alloy #7075-T651
Offset	0 mm.
Dia.	30.9 / 31.6 mm.
Length	357 mm. / Travel 100 mm. 412 mm. / Travel 125 mm. 459 mm. / Travel 150 mm. 499 mm. / Travel 170 mm. 559 mm. / Travel 200 mm.
Weight	580 g / 30.9 * 459 mm. 600 g / 31.6 * 459 mm. (excluding cable set 90 g)
Finish	Polished Black
Shaft finish	Hard Anodized Black

**JD-YSP39J**

ISO MTB / Pat.

33.9 and 34.9 OD with long travel options to provide wider application and size fitment.

Material	Alloy #7075-T651
Offset	0 mm.
Dia.	33.9 / 34.9 mm.
Length	356 mm. / Travel 100 mm. 406 mm. / Travel 125 mm. 456 mm. / Travel 150 mm. 496 mm. / Travel 170 mm. 556 mm. / Travel 200 mm.
Weight	650 g / 33.9 * 456 mm. 685 g / 34.9 * 456 mm. (excluding cable set 90 g)
Finish	Polished Black
Shaft finish	Hard Anodized Black

**JD-YSP15**

ISO MTB / Pat.

Best value ICR (internal cable routing) version offering stealth and clean outlook.

Material	Alloy #6061-T6
Offset	0 mm.
Dia.	30.9 / 31.6 mm.
Length	315 mm. / Travel 80 mm. 360 mm. / Travel 100 mm. 400 mm. / Travel 120 mm. 410 mm. / Travel 125 mm. 470 mm. / Travel 150 mm. 518 mm. / Travel 175 mm. 565 g / 30.9 * 400 mm. (excluding cable set 90 g)
Weight	565 g / 30.9 * 400 mm. (excluding cable set 90 g)
Finish	Polished Black
Shaft finish	Hard Anodized Black

★ stage 2 standard according to suspension system



**JD-YSP38J**

ISO MTB / Pat.

One piece 3D forged shaft 27.2 internal routing dropper post

Material	Alloy #7075-T651
Offset	0 mm.
Dia.	27.2 mm.
Length	315 mm. / Travel 70 mm. 377 mm. / Travel 90 mm. 405 mm. / Travel 110 mm.
Weight	490 g / 27.2 * 405 mm. (excluding cable set 90 g)
Finish	Sandblasted Black
Shaft finish	Hard Anodized Black

**JD-YSP20J**

ISO MTB / ROAD

Unique stealth road style dropper post featuring duo height adjustable, providing clean outlook for Roadies.

Material	Alloy #7075-T651 & SAE4130
Offset	20 mm.
Dia.	27.2 mm.
Adjust Height	35 mm.
Travel	50 mm.
Length	365 mm.
Weight	495 g (excluding cable set 90 g)
Finish	Polished Black
Shaft finish	QPQ

**JD-YSI50**

ISO-MTB / Pat.

**NEW**

Suspension+Dropper. With patented air pressure adjustable system, suspension stiffness can be easily adjusted by allen key to fit with rider's preference.

Material	Alloy #6061-T6 & Alloy 6066-T6
Offset	0 mm.
Dia.	30.9 / 31.6 mm.
Length	364 mm. / Travel 100 mm. 414 mm. / Travel 125 mm. 464 mm. / Travel 150 mm. 504 mm. / Travel 170 mm.
Weight	620 g 31.6 * 504 mm. (excluding cable set 90 g.)
Finish	Polished Black
Shaft finish	Hard Anodized Black
Max. suspension travel	40 mm.







## JD-YSP28

ISO MTB ★ / Pat.

Suspension+Dropper; Combining the comfort of suspension post and the safety of dropper post, suitable for a broad range of bikes. With the unique air pressure adjustable, suspension stiffness can be adjusted easily to fit with different riders' weight and preferences. (Internal version)

<b>Material</b>	Alloy #7075-T651 & SAE4130 (27.2 mm.) Alloy #7075-T651 (30.9 / 31.6 mm.)
<b>Offset</b>	0 mm.
<b>Dia.</b>	27.2 / 30.9 / 31.6 mm.
<b>Damp Ttravel</b>	30 ~ 70 mm.
<b>Length</b>	340 mm. / Travel 80 mm. (27.2 mm.) 390 mm. / Travel 100 mm. (27.2 mm.) 322 mm. / Travel 80 mm. (30.9 / 31.6 mm.) 362 mm. / Travel 100 mm. (30.9 / 31.6 mm.) 402 mm. / Travel 120 mm. (30.9 / 31.6 mm.) 462 mm. / Travel 150 mm. (30.9 / 31.6 mm.) 502 mm. / Travel 170 mm. (30.9 / 31.6 mm.) 562 mm. / Travel 200 mm. (30.9 / 31.6 mm.)
<b>Weight</b>	590 g / 30.9 * 403 mm. 600 g / 27.2 * 390 mm. (excluding cable set 90 g)
<b>Finish</b>	Polished Black Sandblasted Black (27.2 mm.)
<b>Shaft finish</b>	Hard Anodized Black (30.9 / 31.6 mm.) QPQ (27.2 mm.)

★ stage 2 standard according to suspension system



## JD-YSP30

ISO MTB ★ / Pat.

Suspension + Dropper + Air insert External routing version  
Suspension adjustable by inserting air according to pressure and user performance

<b>Material</b>	Alloy #7075-T651 & SAE4130 (27.2 mm.) Alloy #7075-T651 (30.9 / 31.6 mm.)
<b>Offset</b>	0 mm.
<b>Dia.</b>	27.2 / 30.9 / 31.6 mm.
<b>Damp Travel</b>	30 ~ 70 mm.
<b>Length</b>	380 mm. / Travel 100 mm (27.2 mm.) 352 mm. / Travel 100 mm (30.9 / 31.6 mm.) 392 mm. / Travel 120 mm (30.9 / 31.6 mm.)
<b>Weight</b>	610 g / 30.9 * 392 mm (30.9 mm.) 620 g / 27.2 * 380 mm (27.2 mm.) (excluding cable set 90 g)
<b>Finish</b>	Polished Black Sandblasted Black (27.2 mm.)
<b>Shaft finish</b>	Hard Anodized Black (30.9 / 31.6 mm.) QPQ (27.2 mm.)

★ stage 2 standard according to suspension system



## JD-YSP16J

ISO MTB ★ / Pat.

A good balance of comfort and safe ride by combining suspension function with saddle height adjustable.

<b>Material</b>	Alloy #7075-T651 & SAE4130 (27.2 mm.) Alloy #6061-T6 (30.9 / 31.6 mm.)
<b>Offset</b>	10 mm.
<b>Dia.</b>	27.2 / 30.9 / 31.6 mm.
<b>Damp Travel</b>	40 mm.
<b>Length</b>	377 mm. / Travel 50 mm. 417 mm. / Travel 70 mm.
<b>Weight</b>	535 g / 27.2 * 375 mm. (excluding cable set 90 g)
<b>Finish</b>	Polished Black Sandblasted Black (27.2 mm.)
<b>Shaft finish</b>	Hard Anodized Black (30.9 / 31.6 mm.) QPQ (27.2 mm.)

★ stage 1,2 standard according to suspension system



## JD-YS118

ISO MTB

Combination of dropper post and parallelogram suspension that offer the best blend of both worlds. Changeable elastomer stiffness to fit different needs and rider's weight.

<b>Material</b>	Alloy #7075-T651 & SAE4130 (27.2 mm.) Alloy #7075-T651 (30.9 / 31.6 mm.)
<b>Offset</b>	11 mm.
<b>Dia.</b>	27.2 / 30.9 / 31.6 mm
<b>Length</b>	355 mm. / Travel 70 mm. (27.2) 400 mm. / Travel 90 mm. (27.2) 347 mm. / Travel 70 mm. (30.9 / 31.6 mm.) 413 mm. / Travel 100 mm. (30.9 / 31.6 mm.)
<b>Weight</b>	628 g / 27.2*355 mm. 679 g / 27.2*400 mm. 599 g / 31.6 * 347 mm. 660 g / 31.6 * 413 mm. (excluding cable set 90 g)
<b>Finish</b>	Polished Black
<b>Shaft finish</b>	QPQ (27.2 mm.) Hard Anodized Black (30.9 / 31.6 mm.)
<b>Elastomer</b>	#50 / #70 / #90

★ 90 is factory standard #50 / #70 are optional



**JD-YSP19**

ISO MTB ★ / Pat.

External routing dropper post with cable coming out from mid cap for zero cable movement when adjusting the height of post.

<b>Material</b>	Alloy #6061-T6
<b>Offset</b>	0 mm.
<b>Dia.</b>	30.9 / 31.6 mm.
<b>Length</b>	305 mm. / Travel 80 mm. 350 mm. / Travel 100 mm. 400 mm. / Travel 125 mm.
<b>Weight</b>	610 g / 30.9 * 400 mm. (excluding cable set 90 g)
<b>Finish</b>	Polished Black
<b>Shaft finish</b>	Hard Anodized Black

★ stage 2 standard according to suspension system

**JD-YSP29**

ISO MTB / Pat.

150/170 mm travel in external cable routing version to support bike upgrade and routing solution.

<b>Material</b>	Alloy #7075-T651
<b>Offset</b>	0 mm.
<b>Dia.</b>	30.9 / 31.6 mm.
<b>Length</b>	349 mm. / Travel 100 mm. 399 mm. / Travel 125 mm. 449 mm. / Travel 150 mm. 489 mm. / Travel 170 mm.
<b>Weight</b>	610 g / 30.9 * 449 mm. (excluding cable set 90 g)
<b>Finish</b>	Polished Black
<b>Shaft finish</b>	Hard Anodized Black

**JD-YSP22**

ISO MTB ★ / Pat.

External routing dropper post with cable coming out from mid cap for zero cable movement when adjusting the height of post.

<b>Material</b>	Alloy #7075-T651 & SAE4130 (27.2 mm.) Alloy #6061-T6 (30.9 / 31.6 mm.)
<b>Offset</b>	19 mm. (27.2 mm.) 21 mm. (30.9 / 31.6 mm.)
<b>Dia.</b>	27.2 / 30.9 / 31.6 mm.
<b>Length</b>	300 mm. / Travel 65 mm. (27.2 mm.) 350 mm. / Travel 85 mm. (27.2 mm.) 400 mm. / Travel 105 mm. (27.2 mm.) 315 mm. / Travel 80 mm. (30.9 / 31.6 mm.) 360 mm. / Travel 100 mm. (30.9 / 31.6 mm.) 410 mm. / Travel 125 mm. (30.9 / 31.6 mm.)
<b>Weight</b>	605 g / 27.2 * 400 mm. 610 g / 30.9 * 410 mm. (excluding cable set 90 g)
<b>Finish</b>	Polished Black Sandblasted Black (27.2 mm.)
<b>Shaft finish</b>	Hard Anodized Black (30.9 / 31.6 mm.) QPQ (27.2 mm.)


★ stage 2 standard according to suspension system

**JD-YSP36**

ISO MTB / Pat.

One piece 3D forged shaft 27.2 external routing dropper post

<b>Material</b>	Alloy #7075-T651
<b>Offset</b>	0 mm.
<b>Dia.</b>	27.2 mm.
<b>Length</b>	305 mm. / Travel 70 mm. 367 mm. / Travel 90 mm. 395 mm. / Travel 110 mm.
<b>Weight</b>	525 g / 27.2 * 395 mm. (excluding cable set 90 g)
<b>Finish</b>	Sandblasted Black.
<b>Shaft finish</b>	Hard Anodized Black



|| REMOTE LEVER OPTIONS ||

|| J 22.2 / 24 / 31.8 Clamp



J 22.2 Clamp



J 24 Clamp for drop bar



J 31.8 Clamp for drop bar



|| KL



KL2 (I-Spec II mount)

|| MULTI POSITION 1X LEVER ||

|| FL 22.2 Clamp



FL2 (I-Spec II mount)

|| DROP BAR LEVER ||

|| DL 24 Clamp



|| BEARING 1X LEVER ||

|| GL / GLS



GL 22.2 Clamp



GLS 22.2 Clamp



GL2 / GLS2 (I-Spec II mount)